| Name: | Date: | Class: | |
|-------|-------|--------|--|
| | | | |

AST Design Project Worksheet 4

Objectives

| To demonstrate understanding of Archimedes' principle and Pascal's law. To understand the use of storage tanks and the associated problems. To use new material in conjunction with material previously learned in the classroom to answer questions regarding the stability of a storage tank. To use critical thinking to design a solution to an engineering problem. To effectively communicate and present unique ideas to an audience. |
|--|
| Definitions volume |
| mass |
| density |
| buoyancy |
| |
| pressure |
| |
| weight |
| |
| above-ground storage tank (AST) |
| |
| Relationship Questions What is the relationship between the volume, mass, and density? |
| What is the relationship between mass and weight? |

| Naı | me: | Date: | Class: |
|-----|------------------------------------|-------------------------------|--|
| O٠ | uestions | | |
| - | How many hurricanes occurred dur | | orn? g category, effects, landfall location |
| 2. | What U.S. group is responsible for | tracking and predicting weath | ner systems in the tropics? |
| | | | |
| 3. | What types of failure do ASTs expe | rience? What specifically cau | ses these failures? |
| 4. | How does Archimedes' principle ap | oply to ASTs? | |
| 5. | How does Pascal's law apply to AST | -s? | |
| | | | |

| Nar | ne: | Date: | Class: |
|-----|--|--------------------------------|---|
| De | sign Project | | |
| 1. | Derive an equation for the weight of the AST. Hint: Units should be (lb) which is lb_m . If you g | et units of (ft*Ib/s²), you fo | und weight in Ib _f . |
| 2. | Derive an equation for the weight of the liquid Hint: Units should be (lb), which is lb_m . If you g | | bund weight in lb_f). |
| 3. | Derive an equation for the weight of the wate you get units of (ft*lb/s²) you found weight in | | uld be (lb) which is lb _m , if |
| 4. | Use the equations you derived in questions 1, whether or not the AST will displace or remain | - | |

| Name: | Date: | Class: |
|-------|-------|--------|
| | | |

Your Design Criteria

Group 4

| Diameter, d (ft) | 80 |
|--|--|
| Height, h (ft) | 25 |
| Steel type | ASTM A285, Grade C |
| Density of steel, ρ _s (lb/in ³) | 0.284 |
| Shell thickness, t (in) | 0.25 (maximum allowable thickness = 1) |
| Petrochemical type | Benzene |
| Density of petrochemical, ρ _L (kg/m³) | 876.5 |
| Height of petrochemical, L (ft) | 10 |
| Density of water, ρ _w (kg/m³) | 1000 |
| Surge height, S (ft) | 8 |

| 5. Fo | or what purp | oses is this type | of steel commonly | v used? (Cite | vour sources! |
|-------|--------------|-------------------|-------------------|---------------|---------------|
|-------|--------------|-------------------|-------------------|---------------|---------------|

6. What is your petrochemical? What is primarily used for? What are other common names for your petrochemical? (Cite your sources!)

7. According to the equation you derived in question 4, will your AST displace? Show your work.

| Name: _ | | Date: | Class: | |
|---------|--------------|---|---|--|
| a. | If you | our AST displaces (if your AST does not displace, What variables cause the AST to displace? | , skip this question and go to part b): | |
| | ii. | How high should the petrochemical level be petrochemical level is already the height of to so that the AST does NOT displace? | | |
| b. | If you i. | our AST does NOT displace: How high would the surge level need to be so | o that the AST does displace? | |
| | ii. | What other variables can you change so that | the AST does displace? | |

| Name: | Date: | Clacc | |
|---------|-------|--------|--|
| mairic. | Date. | Class. | |

c. Create a graph in Excel that illustrates the weight of the water displaced vs. surge level (S) for 0 < S < h.

Make sure to include: 1) a data marker that indicates the point at which your AST displaces, 2) the weight of the AST + weight of liquid inside AST as a constant value somewhere on your graph, 3) axis titles, 4) axis labels, 5) a clear title and 6) a legend.

8. As a group, come up with at least one idea to prevent displacement OR buckling. Create a schematic diagram or build a miniature prototype to present to the class. (One idea for either displacement or buckling is the minimum. If you would like to come up with an idea for displacement and buckling, or more than one idea, feel free to do so.)

- 9. Prepare a 5- to 8-minute presentation (using PowerPoint or equivalent software) that includes:
 - The dimensions of your group's AST
 - The storm conditions assigned to your group
 - Whether your group's AST displaces or not
 - The graph of weight of the water displaced vs. surge level (S) for 0 < S < h
 - Whether your group's AST will buckle given the storm conditions
 - Your design proposal for a solution to these problems (If you build a miniature prototype, you
 do not need to add this to your PowerPoint, just show the model prototype.)